

## CLAIM LISTING

1. (previously presented) A method for assigning a pilot sequence to communication units within a communication system, the method comprising the steps of:

assigning a first communication unit a first pilot sequence, wherein the first pilot sequence is selected from a group of pilot sequences constructed from a set of Generalized Chirp-Like (GCL) sequences; and

assigning a second communication unit a second pilot sequence taken from the group of pilot sequences constructed from the set of GCL sequences, wherein the first and the second pilot sequences are constructed from the GCL sequences or from sequences resulting from taking a size- $N_G$  unitary transformation of the GCL sequences; and the GCL sequences are generated as

$$S_u = (a_u(0)b, a_u(1)b, \dots, a_u(N_G-1)b),$$

where  $b$  is any complex scalar of unit amplitude and

$$a_u(k) = \exp(-j2\pi u \frac{k(k+1)/2 + qk}{N_G}),$$

where,

$u = 1, \dots, N_G-1$  is known as the “class” of the GCL sequence

$k = 0, 1, \dots, N_G-1$

$q = \text{any integer}$ .

2. (original) The method of claim 1 wherein the step of assigning the first communication unit the first pilot sequence comprises the step of assigning a first base unit the first pilot sequence, and wherein the step of assigning the second communication unit the second pilot sequence comprises the step of assigning a second base unit the second pilot sequence.

3. (original) The method of claim 1 wherein the step of assigning the first communication unit the first pilot sequence comprises the step of assigning a first remote unit the first pilot sequence, and wherein the step of assigning the second communication unit the second pilot sequence comprises the step of assigning a second remote unit the second pilot sequence.

4. (original) The method of claim 1 wherein the step of assigning the first communication unit the first pilot sequence comprises the step of assigning a first sector of a base station the first pilot sequence, and wherein the step of assigning the second communication unit the second pilot sequence comprises the step of assigning a second sector of the base station the second pilot sequence.

5. (original) The method of claim 1 wherein the step of assigning the first communication unit the first pilot sequence comprises the step of assigning a first antenna of a sector of the base station the first pilot sequence, and wherein the step of assigning the second communication unit the second pilot sequence comprises the step of assigning a second antenna of a sector of the base station the second pilot sequence.

6. (original) The method of claim 1 wherein prior to assigning the first and the second communication units the first and the second pilot sequences, performing the step of determining a length of the pilot sequences ( $N_G$ ) based on a number of pilot sequences needed in the communication system ( $K$ ) and a desired pilot sequence length ( $N_p$ ).

7. (original) The method of claim 6 further comprising the step of:  
choosing  $N_G$  to be equal to  $N_p$  if the smallest prime factor of  $N_p$  excluding “1” is larger than  $K$ .

8. (previously presented) A method for assigning a pilot sequence to communication units within a communication system, the method comprising the steps of:

assigning a first communication unit a first pilot sequence, wherein the first pilot sequence is selected from a group of pilot sequences constructed from a set of Generalized Chirp-Like (GCL) sequences;

assigning a second communication unit a second pilot sequence taken from the group of pilot sequences constructed from the set of GCL sequences, wherein prior to assigning the first and the second communication units the first and the second pilot sequences, performing the step of determining a length of the pilot sequences ( $N_G$ ) based on a number of pilot sequences needed in the communication system ( $K$ ) and a desired pilot sequence length ( $N_p$ );

further comprising the step of:

choosing  $N_G$  to be a smallest integer that is greater than  $N_p$  and whose minimum prime factor excluding “1” is larger than  $K$  and generating the set of GCL sequences by truncating sequences in the set to  $N_p$ ; or

choosing  $N_G$  to be a largest integer that is smaller than  $N_p$  and whose minimum prime factor excluding “1” is larger than  $K$ , and generating the set of GCL sequences set by repeating beginning elements of each sequence in the set to append at an end of each sequence to reach the desired length  $N_p$ .

9. (canceled)

10. (previously presented) The method of claim 1 wherein the step of assigning the first communication unit the first pilot sequence comprises the step of assigning the first communication unit a pilot sequence constructed from the class- $u_1$  GCL sequence; and

wherein the step of assigning the second communication unit the second pilot sequence comprises the step of assigning the second communication unit a pilot sequence constructed from the class- $u_2$  GCL sequence that satisfies the requirement of  $|u_1 - u_2|$  being relatively prime to  $N_G$ .

11. (currently amended) A method comprising the steps of:

receiving a pilot sequence as part of an over-the-air transmission, wherein the pilot sequence is constructed from a set of Generalized Chirp-Like (GCL) sequences and is assigned to either a base unit or a remote unit, wherein the pilot sequence is based on a truncated GCL sequence or a cyclically extended GCL sequence; and

utilizing the pilot sequence for at least one of the following:

acquisition and tracking of timing and frequency synchronization, estimation and tracking of desired channels for subsequent demodulation and decoding, estimation and monitoring of characteristics of other channels for handoff purposes, and interference suppression;

wherein the step of receiving the pilot sequence comprises the step of receiving ~~a~~ the pilot sequence constructed from GCL sequences or from sequences resulting from taking a size- $N_G$  unitary transformation of the GCL sequences, and the GCL sequences are generated as

$$S_u = (a_u(0)b, a_u(1)b, \dots, a_u(N_G-1)b),$$

where  $b$  is any complex scalar of unit amplitude and

$$a_u(k) = \exp(-j2\pi u \frac{k(k+1)/2 + qk}{N_G}),$$

where,

$u = 1, \dots, N_G-1$  is known as the “class” of the GCL sequence

$k = 0, 1, \dots, N_G-1$

$q = \text{any integer}$ .

12. (original) The method of claim 11 wherein the step of receiving the pilot sequence comprises the step of receiving the pilot sequence at a base unit.

13. (original) The method of claim 11 wherein the step of receiving the pilot sequence comprises the step of receiving the pilot sequence at a remote unit.

14. (canceled)

15. (currently amended) A communication unit comprising:  
 pilot channel circuitry for transmitting or receiving a first pilot channel sequence,  
 wherein the first pilot channel sequence comprises a sequence from a group of pilot  
 sequences constructed from a set of Generalized Chirp-Like (GCL) sequences and  
 wherein the pilot channel circuitry is further for transmitting or receiving a second pilot  
 channel sequence taken from the group of pilot sequences constructed from the set of GCL  
 sequences and  
 wherein the GCL sequence is equal to

$$S_u = (a_u(0)b, a_u(1)b, \dots, a_u(N_G-1)b),$$

where  $b$  is a complex scalar of unit amplitude and

$$a_u(k) = \exp(-j2\pi t \frac{k(k+1)/2 + qk}{N_G}),$$

where,

$u=1, \dots, N_G-1$  is the “class” of the GCL sequence

$k=0, 1, \dots, N_G-1$

$q=any\ integer.$

16. (canceled)

17. (currently amended) The communication unit of claim 15 further comprising:  
 data channel circuitry for transmitting data, wherein a peak to average power ratio  
 (PAPR) of the first pilot channel sequence is lower than a PAPR of data transmitted over the data  
 channel circuitry.

18. (currently amended) The communication unit of claim 17 wherein the first pilot channel  
 sequence is transmitted at a higher power than the data.

19. (canceled)

20. (previously presented) A method for assigning a pilot sequence to communication units within a communication system, the method comprising the steps of:

assigning a first communication unit a first pilot sequence, wherein the first pilot sequence is selected from a group of pilot sequences constructed from a set of Generalized Chirp-Like (GCL) sequences; and

assigning a second communication unit a second pilot sequence taken from the group of pilot sequences constructed from the set of GCL sequences,

wherein at least one of the following characteristics applies:

the first pilot sequence is constructed from a Generalized Chirp-Like (GCL) sequence of a first class and the second pilot sequence is constructed from a Generalized Chirp-Like (GCL) sequence of a second class,

the second pilot sequence is based on a function of the first sequence and wherein the function of the first sequence is based on at least one of circular shifting of the first sequence and rotating the phase of elements of the first sequence,

the first pilot sequence is of length  $N_p$ , and is based on a truncation of a length  $N_G$  Generalized Chirp-Like (GCL) sequence where  $N_G$  is the smallest prime number that is larger than  $N_p$ , or

the first pilot sequence is of length  $N_p$ , and is based on an extension of a length  $N_G$  Generalized Chirp-Like (GCL) sequence where  $N_G$  is the largest prime number that is smaller than  $N_p$  and the extension is based on appending a repetition of the beginning elements of the GCL sequence to the end to reach the length  $N_p$ .

21. (canceled)

22. (previously presented) The method of claim 20 wherein the first and second communication units each comprise an antenna of a base unit or each comprise an antenna of a remote unit.

23. (previously presented) The method of claim 20

wherein assigning the first communication unit the first pilot sequence comprises

assigning a first antenna of a remote unit the first pilot sequence, and

wherein assigning the second communication unit the second pilot sequence comprises

assigning a second antenna of the remote unit the second pilot sequence.

24. (previously presented) The method of claim 20 wherein the first pilot sequence is based on a truncated Generalized Chirp-Like (GCL) sequence.

25. (canceled)

26. (currently amended) The method of claim 20 A method for assigning a pilot sequence to communication units within a communication system, the method comprising the steps of:  
~~— assigning a first communication unit a first pilot sequence, wherein the first pilot sequence is selected from a group of pilot sequences constructed from a set of Generalized Chirp Like (GCL) sequences; and~~  
~~— assigning a second communication unit a second pilot sequence taken from the group of pilot sequences constructed from the set of GCL sequences, wherein the first pilot sequence is based on a cyclically extended Generalized Chirp-Like (GCL) sequence.~~

27. (canceled)

28. (previously presented) The method of claim 20 wherein the first pilot sequence is assigned to a set of subcarriers in the frequency domain.

29. (previously presented) The method of claim 20 further comprising utilizing by the first communication unit different sequences for transmission at different times in a transmission frame.

30. (previously presented) The method of claim 20 wherein assigning the first communication unit the first pilot sequence comprises assigning the first communication unit a pilot sequence constructed from a class- $u_1$  GCL sequence and

wherein assigning the second communication unit the second pilot sequence comprises assigning the second communication unit a pilot sequence constructed from a class- $u_2$  GCL sequence that satisfies the requirement of  $|u_1 - u_2|$  being relatively prime to  $N_G$ , where  $N_G$  is a length of the GCL sequence from which the first pilot sequence is constructed.

31. (previously presented) The method of claim 26 wherein the first and second communication units each comprise an antenna of a base unit or each comprise an antenna of a remote unit.

32. (previously presented) The method of claim 26 wherein assigning the first communication unit the first pilot sequence comprises assigning a first antenna of a remote unit the first pilot sequence, and wherein assigning the second communication unit the second pilot sequence comprises assigning a second antenna of the remote unit the second pilot sequence.
33. (previously presented) The method of claim 26 wherein the first pilot sequence is assigned to a set of subcarriers in the frequency domain.
34. (previously presented) The method of claim 26 further comprising utilizing by the first communication unit different sequences for transmission at different times in a transmission frame.
35. (currently amended) A method for assigning a pilot sequence to communication units within a communication system, the method comprising the steps of:  
assigning a first communication unit a first pilot sequence, wherein the first pilot sequence is selected from a group of pilot sequences constructed from a set of Generalized Chirp-Like (GCL) sequences; and  
assigning a second communication unit a second pilot sequence taken from the group of pilot sequences constructed from the set of GCL sequences, wherein the first pilot sequence is based on a cyclically extended Generalized Chirp-Like (GCL) sequence.  
~~The method of claim 26~~ wherein assigning the first communication unit the first pilot sequence comprises assigning the first communication unit a pilot sequence constructed from a class- $u_1$  GCL sequence and  
 wherein assigning the second communication unit the second pilot sequence comprises assigning the second communication unit a pilot sequence constructed from a class- $u_2$  GCL sequence that satisfies the requirement of  $|u_1 - u_2|$  being relatively prime to  $N_G$ , where  $N_G$  is a length of the GCL sequence from which the first pilot sequence is constructed.